

TP 101 Tripod pješačka barijera



TP 101 Specifikacije

Power Requirements	110/220V. 60/50Hz. AC (%±10), 24V DC. At standby ~11W. max. ~60W.
Dimensions	380 x 300 (+ kol boyu 470) x 955 mm
Arms	Ø40 x 2 mm 304-Grade (Opt. 316-Grade) stainless steel (Opt. anodised hard aluminium). Arms can be dismantled or mounted one by one separately.
Body Features	304-Grade (Opt. 316-Grade) stainless steel surface, flat and angular top lid versions with protection against water for outdoors use.
Indicator Features	Green Arrow & Red Cross LED as a standard feature.
Operating Temperature, Humidity, IP Rating, MCBF	-20°C to +68°C (Opt. -50°C with heater unit) / RH 95% non-condensing IP 54 Outdoor Model (Opt. IP 56) / 1M Cycles
Control System	All inputs are opto-coupler protected. Controlled by dry contact or grounding input. Compatible with all access control systems that provide dry contact or grounding outputs. Optional RS232/RS485/TCP IP control module is available.
Operation	Bi-directional passage, manually (Opt. Motorized) operated system.
Output Data	The system provides dry contact passage feedback by relays.
Emergency Mode	The rotor spins freely to allow free passage (Fail Safe default). Fail lock option is available.
Flow Rate	Capacity of Mechanism - Manual System: ~97+97 passages/minute Nominal: ~41+41 passage-per-minute Motorized System: ~48+48 passages/minute Nominal: ~ 29+29 passages/minute (Recommended reference figure) Explanatory Notes: - The above given figures are approximate for one person per walkway or lane. - The system allows the new passage authorisation in less than ~0, 3 seconds. After the passage authorization, the total passage time depends on the pushing and passage speed of the people. - Utilisation of different access control units can change the flow rate.
Standard Features	Cut-out and acrylic cover for card reader mounting (when requested at the time of purchase order).
Optional Accessory and Applications	Remote control units, interface unit for PC, RS485, RS232 and LAN, counter, automatic drop (retractable) arm, alarm sensor, card reader pole, heater positive unit, special design top lid, separator, floor mounting plate.

TP 101 Tehnički nacrt

